

Vibration Tester TV110



- Analysis acceleration, velocity, and displacement
- For checking of unbalance, misalignment, bearings and gears
- Large memory of 100 results and 10 frequency spectrograms
- Includes a hand-held accelerometer probe with a removable magnetic base
- Rechargeable battery
- Large LCD display all functions and parameters
- Upper and lower limit setting and sound alarm
- Printer included

Technical specifications

Acceleration	Peak value from 0.1 to 199.9 (m/s ²)	Frequency range 10Hz to 500Hz 10Hz to 1KHz 10Hz to 10KHz
Velocity	RMS from 0.01 to 19.99 (cm/s)	Frequency range 10Hz to 500Hz 10Hz to 1KHz
Displacement	Peak to peak from 0.001 to 1.999 (mm)	Frequency range 10Hz to 500Hz
Operating temperature	0 - 40	
Power supply	Nickel-cadmium battery 4×1.25V rechargeable	
Dimensions	270mm×86mm×47mm	
Weight	650g	

Standard delivery

- Main unit with removable printer 1
- Accelerometer probe 1
- Magnetic base 1
- Battery charger 1
- TIME certificate 1
- Instruction manual 1
- Warranty card 1
- Carrying case

Optional accessories

- Probe groupware
- Long needle